

LUCA-40KM

600 DPI COLOR RETRANSFER
IDENTIFICATION CARD PRINTER



**CARD
PLUS** 



LUCA-40KM



Print Method	Color dye Sublimation retransfer technology
Print Resolution	600 DPI
Print Capability	Single Side, Double Side, Over-the-Edge, Photo quality
Cards Supported	PVC, ABSS, PET, PET-G, PC; 85.6 x 53.98mm (ISO ID-1/CR-80 size)
Card Thickness	0.5- 1.0 mm thickness
Card Loading	Auto card feeder
Security Features	Own technology SOC, RFID ribbon, card feeder lock
User Friendliness	Easy to replace consumable
Print Speed	Single Side : 25 secs; Double Side : 55 secs
Card Capacity	Auto Feeder : 250 cards (0.76mm thickness); Manual Feed
Interfaces	USB 2.0, Ethernet 10/100 Duplex mode
Operating Environment	Temperature : 15- 30 ; Humidity : 35- 95%
Storage Environment	Temperature : 5- 45 ; Humidity : 35- 96%
Certificates	UL, FCC, CE, KCC and CCC
Warranty	3 year Warranty, Lifetime for Print Head
Power Supply	Auto wide ranging 100-240V, 50/60 Hz
Dimensions	12.25" (L) x 13.25" (W) x 17" (H)
Weight	22 kg (48 lbs)
Driver	Windows 32 and 64 bit, Windows 7,8,10
Options	RFID R/W, MSR R/W, SAM R/W
Consumables	YMCK, YMCS : 500 imges YMCKK, YMCSK, YMCFK : 400 imges Retransfer film (500 imges) with cleaning roller
Cleaning Set	Cleaning Card, Cleaning Roller and Cleaning Swabs
Layered Durability and Security Features	Retransfer Film with built in Generic Hologram Overlay or Patch (Optional) Retransfer Film with built in Custom Hologram Overlay or Patch (Optional) No need for an additional laminator